



# Product Information Sheet



Sheet Number: **0062**

Rev 22-11-06

## ROOFBOND Shieldseal W Plus

Acrylic water based roof sealer

**Shieldseal W Plus** is an acrylic sealer designed to penetrate and prime in preparation for Roofbond roof coatings to follow. Shieldseal W Plus is airless sprayed using a 517 tip and dries clear.

**General Application Guide:** Spray 1 coat of Shieldseal W Plus with airless spray gun after cleaning and repair steps listed in the Roofbond application sheet.

Suitable for Colorbond®, Zinalume® and Fibre Cement Sheeting.



### Specifications:

(dry times are considered at 25°)

#### Roofbond Shieldseal W Plus:

**Surface Dry:** 1/2-2 hours

**Top Coat:** 2-4 hours

**Hard Dry:** 3 -5 days

**Wet Film Thickness:** N/A

**Dry Film Thickness:** N/A

**Thinning:** No thinning required normally. If desired thin with water sparingly.

**Clean Up:** Clean up with water



Top Picture: Shieldseal W Plus being sprayed over ColorBond® metal roofing.

Bottom Picture: Spraying Roofbond roof paint over Shieldseal W Plus.

Primer Plus comes in 15 litre pails.

See **MSDS** for safety information

### Features:

Penetrating Primer

Clear Colour

Flexible

Easy To Apply

Promotes Adherence

Pre Mixed

Binds Chalkiness of surface

### Benefits:

Good Adhesion

Dries clear

Allows for some substrate move-

Airless Sprayed

Job flows with ease

Stirring only required

Paint adheres well

**Notes:** There are many substrates on the market. Please consult Shieldcoat for further information regarding applications not on this sheet.