



Product Information Sheet



Sheet Number: **0065**

Rev 22-11-06

ROOFBOND Rustshield T

Acrylic solvent based 2 part anti- rust roof sealer

Rustshield T is an acrylic anti-rust sealer/ primer deigned to penetrate and prime in preparation for Roofbond roof coatings to follow. Rustshield T is airless sprayed using a 517 tip and dries clear.



General Application Guide:

Mix two components of Rustshield T together on site and use immediately. Spray 1 coat of Rust Shield T with airless spray gun and a 517-521 tip after cleaning and repair steps listed in the Roofbond application sheet.

Suitable for Colorbond®, Zinalume® and Rusty Galvanised Sheeting.

Specifications:

(dry times are considered at 25°)

Roofbond Rustshield W :

Surface Dry: 2 hours

Top Coat: 24 hours

Hard Dry: 3 -5 days

Wet Film Thickness: 60 microns

Dry Film Thickness: 20 microns

Thinning: No thinning required normally. If desired thin with xylene thinners sparingly.

Clean Up: Clean up with thinners or turpentine

Top Picture: Rustshield T being sprayed over galvanised metal roofing.

Rustshield T comes in 20 litre pails plus additive.

See MSDS for safety information

Features:

Anti- Rust Primer

Grey Colour

Flexible

Easy To Apply

Promotes Adherence

Pre Mixed

Binds Chalkiness of surface

Benefits:

Eliminates Rust

Dries a clear

Allows for some substrate move-

Airless Sprayed

Job flows with ease

Stirring only required

Paint adheres well

Notes: There are many substrates on the market. Please consult Shieldcoat for further information regarding applications not on this sheet.