



# Product Information Sheet



Sheet Number: **003 I**

Rev 22-11-06

## STENCILSHIELD Primer Plus

### Acrylic water based Driveway Stencil Coating

**STENCILSHIELD Primer Plus** is an acrylic primer designed to penetrate concrete in preparation for Stencilshield coatings to follow. Primer Plus must be rolled with a nap roller and dries clear.

**General Application Guide:** Roll 1 coat of primer Plus with a nap roller only after cleaning and repair steps listed in the Stencilshield application sheet.



#### Specifications:

(dry times are considered at 25°)

#### Stencilshield Primer Plus:

**Surface Dry:** 1/2-2 hours

**Top Coat:** 2-4 hours

**Hard Dry:** 3 -5 days

**Wet Film Thickness:** N/A

**Dry Film Thickness:** N/A

**Thinning:** No thinning required normally. If desired thin with water sparingly.

**Clean Up:** Clean up with water



Top Picture: Stencilshield Primer Plus applied to prepared concrete.

Bottom Picture: Primer Plus dry and stencil pattern laid.

Primer Plus comes in 15 litre pails.

**See MSDS for safety information**

## Features:

Penetrating Primer

Clear Colour

Flexible

Easy To Apply

Promotes Stencilshield Adherence

Pre Mixed

Crack Bridges

## Benefits:

Good Adhesion

Dries clear

Allows for some substrate move-

Nap Roller Applied

Job flows with ease

Stirring only required

Will not Delaminate near cracks

**Notes:** There are many substrates on the market. Please consult Shieldcoat for further information regarding applications not on this sheet.