



# Product Information Sheet



Sheet Number: **0072**  
Rev 15-06-2010



## TERRABOND

Acrylic water based non-glazed terracotta clear coating

### Terrabond

is an acrylic coating deigned to seal and produce a clear gloss to non- factory glazed terracotta tile roofs. It is applied by airless spray using a 517-521 tip size.

### General Application Guide:

Apply one coat of Shieldseal W sealer and 1-2 thin coats of Terrabond using an airless spray gun.

### Non-Glazed Terracotta Tile:

- Apply Mouldshield C to remove any mould (optional)
- Water blast roof with at least 3000 p.s.i.
- Apply one coat of Shieldseal W with 517 airless tip
- Apply 1 thin coat of Terrabond with 517-521 airless tip
- Allow to totally dry between coats, recommended time 12 hours before applying second coat, if required



### Specifications:

(all dry times are considered at 25° C and at 50% humidity)

#### Roofbond Shieldseal W:

**Surface Dry:** 4 -5 hours

**Top Coat:** 12 hours

**Hard Dry:** 4 -5 days

**Wet Film Thickness:** Approx. 180 microns

**Dry Film Thickness:** Approx. 90 microns

**Thinning:** No thinning required normally. If desired thin with water sparingly.

**Clean Up:** Water



### Features:

- Good Adhesion
- Dries Clear
- Flexible
- Easy To Apply
- Durable
- Pre Mixed
- Not Recommended over glazed tiles

### Benefits:

- Prepares Substrate
- Water based
- Allows for some substrate move-
- Airless Sprayed
- Part of a warranty for 10 years
- Glaze finish
- Environmentally friendly

Shieldcoat has become the first paint manufacturer in Australia to meet the international environmental standard, ISO 14001